OUTDOOR SPORTS FLOORING

SMARTFLOOR-EX

Outdoor resilient and fast-applied acrylic sports flooring system ideal for tennis, basketball, volleyball, handball, football courts, as well as any other outdoor sports courts.

Combination of wet-pour acrylic coatings in total average thickness of 1.5mm.




Steps:

- 1. RITIVEX R LIQUID 1102 Acrylic primer.
 - Used as primer of acrylic coatings such as **SMARTCOAT 880**. Applied by airless sprayer or brush.
- 2.SMARTCOAT 880 Acrylic, colored coating/filler for smoothing out the surface of the asphalt and for giving superior wearing properties and mechanical resistance to the system.

Consists of colored acrylic resins, quartz sand and special improver. **SMARTCOAT 880** is applied by squeegee on smooth, compact road-grade asphalt and in parallel seals the porosity of the asphalt and smooths out the surface. Highly resistant to adverse weather conditions (snow, frost, heat waves etc.) after drying.

3. SMART TOP 890 - Acrylic, elastic coating for indoor and outdoor surfaces.

Applied by squeegee and rollers.



Description	Consumption
RITIVEX R LIQUID 1102 - Acrylic primer.	0.2-0.3kg/m ² for 1 layer
SMARTCOAT 880 - Acrylic, colored coating/filler for smoothing out the surface of the asphalt and for giving superior wearing properties and mechanical resistance to the system.	2kg/m ² for 2 layers depending on the porosity of the substrate
SMART TOP 890 - Acrylic, elastic coating for indoor and outdoor surfaces.	0.3kg/m ² per layer